











Composition Composición	100% Solution Dyed Acrylic 100% Acrílico Tintado en Masa	Uses Usos
Width Ancho	153 cm	
Weight Peso	310 g/m ²	
Length of rolls Longitud de las piezas	50 ml	
Finish Acabado	Water repellent. Anti-stain treatment Hidrófugo con tratamiento anti-manchas	
Colour fastness to light Solidez a la luz	7/8 UNE EN ISO 105-B02:2014	Qualities Cualidades
Colour fastness to artificial weathering Solidez del color a la intemperie artificial	4/5 UNE EN ISO 105-B04:1998	
Colour fastness to chlorinated water Solidez de las tinturas al agua clorada	5/5 UNE EN ISO 105-E03:2010	
Ultraviolet protection factor UPF Factor de protección ultravioleta UPF	50+ AZ/NZS 4399/1996	
Spray test	5/5 UNE EN ISO 24920	
Water column mm Columna de agua mm	650 UNE EN ISO 20811	
Tear resistance Resistencia al desgarrar	Warp Urdimbre 49 N Weft Trama 32 N UNE EN ISO 13937-3:2001	
Slippage resistant Deslizamiento a la costura	Warp Urdimbre 5,0 mm Weft Trama 3,0 mm UNE EN ISO 13936-2:2004	
Tensile strength Resistencia a la tracción	Warp Urdimbre 1800 N Weft Trama 860 N UNE EN ISO 13934-1:2013	
Shrinkage to washing Encogimiento al lavado	Warp Urdimbre -1'5% Weft Trama 0% UNE EN ISO 5077:2007	
Cleaning instructions Manutención		

Sensitive values of tolerance +/- 5% Valores susceptibles de tolerancia de +/- 5%



The Agora warranty covers the fabric becoming unserviceable as a result of loss of colour or strength from normal exposure conditions, including sunlight, mildew, rot and atmospheric chemicals, when properly installed, used and maintained. The warranty does not cover labour and installation costs supplied by the dealer. The warranty neither applies against deterioration of any kind due to abusive use, accidental burns, negligence or perforations.
La garantía Agora cubre un anormal deterioro del tejido debido a la pérdida de color o resistencia siempre que existan unas condiciones de exposición normales, incluyendo el sol, moho, putrefacción y químicos de la atmósfera en general, siempre y cuando el tejido haya sido instalado, utilizado y mantenido correctamente. La garantía no cubre los trabajos de instalación del distribuidor. La garantía tampoco cubre, en cualquier caso, el deterioro debido al uso abusivo, quemaduras accidentales, negligencia o perforación.