





























Composition Composición	Solution Dyed Acrylic + Recycled Acrílico tintado en masa + Reciclado	Uses Usos
Weight Peso	363 g/m ² 10.7 oz/yd ²	 
Width Ancho	160 cm 63"	 
Length of Roll Longitud de las piezas	30 m 32.8 yd	 
Finish Acabado	 Water Repellent Hidrófugo  Anti-Stain Antimanchas  Eco-Shield No PFAs  Soft Suave	 
Colour Fastness to Light Solidez del color a la luz	7/8 UNE EN ISO 105-B02:2014	
Colour Fastness to Artificial Weathering Solidez del color a la interperie artificial	7/8 UNE EN ISO 105-B04:1998	
Colour Fastness to Rubbing Solidez del color al frote	4-5/5 UNE EN ISO 105-X12:2016	Qualities Cualidades
Colour Fastness to Chlorinated Water Solidez del color al agua clorada	5/5 UNE EN ISO 105-E03:2010	 WATER REPELLENT HIDROFUGO
Ultraviolet Protection Factor UPF Factor de protección ultravioleta UPF	50+ AZ/NZS 4399/1996	 STAIN RESISTANT ANTIMANCHAS
Spray Test	5/5 UNE EN ISO 24920	 MOULD RESISTANT ANTIMOHO
Water Column mm Columna de agua mm	180 UNE EN ISO 20811	 UV PROTECT PROTECCIÓN UV
Tear Resistance Resistencia al desgarro	Warp Urdimbire 170 N Weft Trama 150 N UNE EN ISO 13937-3:2001	 UV RESISTANT RESISTENCIA UV
Slippage Resistance Deslizamiento a la costura	Warp Urdimbire 5,0 mm 0.19" Weft Trama 3,0 mm 0.12" UNE EN ISO 13936-2:2004	 DURABLE DURADERO
Tensile Strength Resistencia a la tracción	Warp Urdimbire 1800 N Weft Trama 900 N UNE EN ISO 13934-1:2013	 EASY TO CLEAN FÁCIL DE LIMPIAR
Resistance to Pilling Resistencia al pilling	4/5 UNE EN ISO 12945-2:2001	 BREATHABLE TRANSPIRABLE
Abrasion Resistance (Martindale) Resistencia a la abrasión (Martindale)	20.000 UNE EN ISO 12497-2:2016	 BLEACH friendly
Shrinkage to Washing Encogimiento al lavado	Warp Urdimbire -1,5% Weft Trama 0% UNE EN ISO 5077:2007	 DURABLE is green
Flammability Inflamabilidad	UNE 1021 PART 1 BS 5852-0 Cigarette Test Cal 117, NFPA 260	Optional Finishes Acabados opcionales
Cleaning Instructions Manutención	    	 WATERPROOF IMPERMEABLE

Sensitive values of tolerance +/- 5%. Valores susceptibles de tolerancia de +/- 5%.

Due to the recycling process of LIFE products, colours may vary slightly from batch to batch.
Debido al proceso de reciclado de los productos LIFE, los colores pueden variar ligeramente de un lote a otro.

5 YEARS WARRANTY

The Agora warranty covers the fabric becoming unserviceable as a result of loss of colour or strength from normal exposure conditions, including sunlight, mildew, rot and atmospheric chemicals, when properly installed, used and maintained. The warranty does not cover labour and installation costs supplied by the dealer. The warranty neither applies against deterioration of any kind due to abusive use, accidental burns, negligence or perforations. La garantía Agora cubre un anormal deterioro del tejido debido a la pérdida de color o resistencia siempre que existan unas condiciones de exposición normales, incluyendo el sol, moho, putrefacción y químicos de la atmósfera en general, siempre y cuando el tejido haya sido instalado, utilizado y mantenido correctamente. La garantía no cubre los trabajos de instalación del distribuidor. La garantía tampoco cubre, en cualquier caso, el deterioro debido al uso abusivo, quemaduras accidentales, negligencia o perforación.

