

Composition Composición	70% Solution Dyed Acrylic 70% Acrílico Tintado en Masa 30% PES FR
Width Ancho	300 cm 118"
Weight Peso	148 g/m² 4.4 oz/yd ²
Length of rolls Longitud de las piezas	50 m 54.7 yd Full width. Al ancho.
Finish Acabado	 Water Repellent Hidrófugo  Anti-Stain Antimanchas  Soft Suave
Colour fastness to light Solidez a la luz	7-8/8 UNE EN ISO 105-B02:2014
Colour fastness to artificial weathering Solidez del color a la intemperie artificial	7-8/8 UNE-EN ISO 105-B04:1998
Colour fastness to rubbing Solidez de las tinturas al frote	4-5/5 UNE EN ISO 105-X12:2016
Colour fastness to chlorinated water Solidez de las tinturas al agua clorada	5/5 UNE EN ISO 105-E03:2010
Ultraviolet protection factor UPF Factor de protección ultravioleta UPF	50+ AZ/NZS 4399/1996
Tear resistance Resistencia al desgarro	Warp Urdimbre 29 N Weft Trama 48 N UNE EN ISO 13937-3:2001
Slippage resistant Deslizamiento a la costura	Warp Urdimbre 6,0 mm 0.24" Weft Trama 6,0 mm 0.24" UNE EN ISO 13936-2:2004
Tensile strength Resistencia a la tracción	Warp Urdimbre 480 N Weft Trama 970 N UNE EN ISO 13934-1:2013
Shrinkage to washing Encogimiento al lavado	Warp Urdimbre -1'5% Weft Trama 0% UNE EN ISO 5077:2007
Flammability Inflamabilidad	UNE 1021 PARTS 1 BS 5852 Cigarette & Match Cal 117
Cleaning instructions Manutención	    

Uses

Usos



Qualities

Cualidades



Sensitive values of tolerance +/- 5%. Valores susceptibles de tolerancia de +/- 5%



The Agora warranty covers the fabric becoming unserviceable as a result of loss of colour or strength from normal exposure conditions, including sunlight, mildew, rot and atmospheric chemicals, when properly installed, used and maintained. The warranty does not cover labour and installation costs supplied by the dealer. The warranty neither applies against deterioration of any kind due to abusive use, accidental burns, negligence or perforations.
La garantía Agora cubre un anormal deterioro del tejido debido a la pérdida de color o resistencia siempre que existan unas condiciones de exposición normales, incluyendo el sol, moho, putrefacción y químicos de la atmósfera en general, siempre y cuando el tejido haya sido instalado, utilizado y mantenido correctamente. La garantía no cubre los trabajos de instalación del distribuidor. La garantía tampoco cubre, en cualquier caso, el deterioro debido al uso abusivo, quemaduras accidentales, negligencia o perforación.