

Composition Composición		Solution Dyed Acrylic + Recycled Acrílico tintado en masa + Reciclado		Uses Usos	
Weight Peso		270 g/m² 8.0 oz/y²		    	
Width Ancho		160 cm 63"			
Lenght of Roll Longitud de las piezas		50 ml 54.7 yd			
Finish Acabado		 Water Repellent Hidrófugo  Eco-Shield No PFAs  Anti-Stain Antimanchas  Soft Suave			
Colour Fastness to Light Solidez del color a la luz		7/8 UNE EN ISO 105-B02:2014			
Colour Fastness to Artificial Weathering Solidez del color a la interperie artificial		7/8 UNE EN ISO 105-B04:1998		Qualities Cualidades WATER REPELLENT HIDROFUGO STAIN RESISTANT ANTIMANCHAS MOULD RESISTANT ANTIMOHO UV PROTECT PROTECCIÓN UV UV RESISTANT RESISTENCIA UV DURABLE DURADERO EASY TO CLEAN FÁCIL DE LIMPIAR BREATHABLE TRANSPIRABLE	
Colour Fastness to Rubbing Solidez del color al frote		4-5/5 UNE EN ISO 105-X12:2016			
Colour Fastness to Chlorinated Water Solidez del color alagua clorada		5/5 UNE EN ISO 105-E03:2010			
Ultraviolet Protection Factor UPF Factor de protección ultravioleta UPF		50+ AZ/NZS 4399/1996			
Spray Test		5/5 UNE EN ISO 24920			
Water Column mm Columna de agua mm		180 UNE EN ISO 20811		BLEACH friendly DURABLE is green	
Tear Resistance Resistencia al desgarro		Warp Urdimbre 170 N Weft Trama 150 N UNE EN ISO 13937-3:2001			
Slippage Resistance Deslizamiento a la costura		Warp Urdimbre 5,0 mm 0.19" Weft Trama 3,0 mm 0.12" UNE EN ISO 13936-2:2004			
Tensile Strenght Resistencia a la tracción		Warp Urdimbre 1800 N Weft Trama 900 N UNE EN ISO 13934-1:2013			
Resistance to Pilling Resistencia al pilling		4/5 UNE EN ISO 12945-2:2001			
Abrasion Resistance (Martindale) Resistencia a la abrasión (Martindale)		20.000 UNE EN ISO 12497-2:2016		Optional Finishes Acabados opcionales WATERPROOF IMPERMEABLE	
Shrinkage to Washing Encogimiento al lavado		Warp Urdimbre -1,5% Weft Trama 0% UNE EN ISO 5077:2007			
Flammability Inflamabilidad		UNE 1021 PART 1 BS 5852-0 Cigarette Test Cal 117, NFPA 260			
Cleaning Instructions Manutención					

Sensitive values of tolerance +/- 5%.
Valores susceptibles de tolerancia de +/- 5%.

Due to the recycling process of LIFE products, colours may vary slightly from batch to batch.

Debido al proceso de reciclado de los productos LIFE, los colores pueden variar ligeramente de un lote a otro.

5 YEARS WARRANTY

The Agora warranty covers the fabric becoming unserviceable as a result of loss of colour or strength from normal exposure conditions, including sunlight, mildew, rot and atmospheric chemicals, when properly installed, used and maintained. The warranty does not cover labour and installation costs supplied by the dealer. The warranty neither applies against deterioration of any kind due to abusive use, accidental burns, negligence or perforations. La garantía Agora cubre un anormal deterioro del tejido debido a la pérdida de color o resistencia siempre que existan unas condiciones de exposición normales, incluyendo el sol, moho, putrefacción y químicos de la atmósfera en general, siempre y cuando el tejido haya sido instalado, utilizado y mantenido correctamente. La garantía no cubre los trabajos de instalación del distribuidor. La garantía tampoco cubre, en cualquier caso, el deterioro debido al uso abusivo, quemaduras accidentales, negligencia o perforación.

