






























|  |   |   |
|--|---|---|
| Composition<br>Composición   | 100% Solution Dyed Acrylic<br>100% Acrílico tintado en masa   | Uses<br>Usos  |
| Weight<br>Peso   | 280 g/m <sup>2</sup><br>8.3 oz/yd <sup>2</sup>  |     |
| Width<br>Ancho   | 160 cm<br>63"   |     |
| Rapport  | 28,57 cm<br>11,25"  |     |
| Length of Roll<br>Longitud de las piezas   | 50 ml<br>54.7 yd  |    |
| Finish<br>Acabado  |  Water Repellent<br>Hidrófugo  Anti-Stain<br>Antimanchas<br> Eco-Shield<br>No PFAs  |   |
| Colour Fastness to Light<br>Solidez del color a la luz                                   | 7-8/8<br>UNE EN ISO 105-B02:2014  | Qualities<br>Cualidades   |
| Colour Fastness to Artificial Weathering<br>Solidez del color a la interperie artificial | 7-8/8<br>UNE EN ISO 105-B04:1998  |  WATER REPELLENT<br>HIDROFUGO  STAIN RESISTANT<br>ANTIMANCHAS   |
| Colour Fastness to Rubbing<br>Solidez del color al frote                                 | 4-5/5<br>UNE EN ISO 105-X12:2016  |  MOULD RESISTANT<br>ANTIMOHO  UV PROTECT<br>PROTECCIÓN UV   |
| Colour Fastness to Chlorinated Water<br>Solidez del color al agua clorada                | 5/5<br>UNE EN ISO 105-E03:2010  |  UV RESISTANT<br>RESISTENCIA UV  DURABLE<br>DURADERO  |
| Ultraviolet Protection Factor UPF<br>Factor de protección ultravioleta UPF               | 50+<br>AZ/NZS 4399/1996   |  EASY TO CLEAN<br>FÁCIL DE LIMPIAR  BREATHABLE<br>TRANSPIRABLE  |
| Spray Test   | 5/5<br>UNE EN ISO 4920  |   |
| Tear Resistance<br>Resistencia al desgarro   | Warp Urdimbire 170 N<br>Weft Trama 150 N<br>UNE EN ISO 13937-3:2001   |   |
| Slippage Resistance<br>Deslizamiento a la costura  | Warp Urdimbire 5,0 mm 0.19"<br>Weft Trama 3,0 mm 0.12"<br>UNE EN ISO 13936-2:2004   |  DURABLE<br>is green  PFAS<br>free  BLEACH<br>friendly |
| Tensile Strength<br>Resistencia a la tracción  | Warp Urdimbire 1900 N<br>Weft Trama 950 N<br>UNE EN ISO 13934-1:2013  |   |
| Resistance to Pilling<br>Resistencia al pilling  | 4-5/5<br>UNE EN ISO 12945-2:2001  |   |
| Abrasion Resistance (Martindale)<br>Resistencia a la abrasión (Martindale)               | 20000<br>UNE EN ISO 12497-2:2016  | Optional Finishes<br>Acabados opcionales  |
| Shrinkage to Washing<br>Encogimiento al lavado   | Warp Urdimbire -1,5%<br>Weft Trama 0%<br>UNE EN ISO 5077:2007   |  WATERPROOF<br>IMPERMEABLE   |
| Flammability<br>Inflamabilidad   | UNE 1021 PART 1<br>BS 5852-0 Cigarette Test<br>Cal 117, NFPA 260  |  EXTRA SOFTNESS<br>SUAVIDAD EXTRA  |
| Cleaning Instructions<br>Manutención   |      |  FLAME RETARDANT<br>IGNIFUGADO   |

Sensitive values of tolerance +/- 5%. Valores susceptibles de tolerancia de +/- 5%

Waterproof and flame retardant finishes: Recommended for cushions and upholstery only.

Acabados Waterproof y FR: Recomendado únicamente para cojines y tapicería.

**5 YEARS WARRANTY**

The Agora warranty covers the fabric becoming unserviceable as a result of loss of colour or strength from normal exposure conditions, including sunlight, mildew, rot and atmospheric chemicals, when properly installed, used and maintained. The warranty does not cover labour and installation costs supplied by the dealer. The warranty neither applies against deterioration of any kind due to abusive use, accidental burns, negligence or perforations. La garantía Agora cubre un anormal deterioro del tejido debido a la pérdida de color o resistencia siempre que existan unas condiciones de exposición normales, incluyendo el sol, moho, putrefacción y químicos de la atmósfera en general, siempre y cuando el tejido haya sido instalado, utilizado y mantenido correctamente. La garantía no cubre los trabajos de instalación del distribuidor. La garantía tampoco cubre, en cualquier caso, el deterioro debido al uso abusivo, quemaduras accidentales, negligencia o perforación.