

|                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Composition<br>Composición                                                               | 100% Solution Dyed Acrylic<br>100% Acrílico tintado en masa                                                                                                                                                                                                                                                                                                                                                                           | Uses<br>Usos                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Weight<br>Peso                                                                           | 280 g/m <sup>2</sup><br>8.3 oz/y <sup>2</sup>                                                                                                                                                                                                                                                                                                                                                                                         |  <br> <br> <br> <br>  |
| Width<br>Ancho                                                                           | 160 cm<br>63"                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Length of Roll<br>Longitud de las piezas                                                 | 50 m<br>54.7 yd                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Finish<br>Acabado                                                                        |  Water Repellent<br>Hidrófugo  Anti-Stain<br>Antimanchas                                                                                                                                                                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Colour Fastness to Light<br>Solidez del color a la luz                                   | 7-8/8<br>UNE EN ISO 105-B02:2014                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Colour Fastness to Artificial Weathering<br>Solidez del color a la interperie artificial | 7-8/8<br>UNE EN ISO 105-B04:1998                                                                                                                                                                                                                                                                                                                                                                                                      | Qualities<br>Cualidades                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Colour Fastness to Rubbing<br>Solidez del color al frote                                 | 4-5/5<br>UNE EN ISO 105-X12:2016                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Colour Fastness to Chlorinated Water<br>Solidez del color al agua clorada                | 5/5<br>UNE EN ISO 105-E03:2010                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Ultraviolet Protection Factor UPF<br>Factor de protección ultravioleta UPF               | 50+<br>AZ/NZS 4399/1996                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Spray Test                                                                               | 5/5<br>UNE EN ISO 24920                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Tear Resistance<br>Resistencia al desgarro                                               | Warp Urdimbre 170 N<br>Weft Trama 150 N<br>UNE EN ISO 13937-3:2001                                                                                                                                                                                                                                                                                                                                                                    | <br>WATER REPELLENT<br>HIDRÓFUGO <br>STAIN RESISTANT<br>ANTIMANCHAS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Slippage Resistance<br>Deslizamiento a la costura                                        | Warp Urdimbre 5,0 mm 0.19"<br>Weft Trama 3,0 mm 0.12"<br>UNE EN ISO 13936-2:2004                                                                                                                                                                                                                                                                                                                                                      | <br>MOULD RESISTANT<br>ANTIMOHO <br>UV PROTECT<br>PROTECCIÓN UV                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Tensile Strength<br>Resistencia a la tracción                                            | Warp Urdimbre 1600 N<br>Weft Trama 800 N<br>UNE EN ISO 13934-1:2013                                                                                                                                                                                                                                                                                                                                                                   | <br>UV RESISTANT<br>RESISTENCIA UV <br>DURABLE<br>DURADERO                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Resistance to Pilling<br>Resistencia al pilling                                          | 4-5/5<br>UNE EN ISO 12945-2:2001                                                                                                                                                                                                                                                                                                                                                                                                      | <br>EASY TO CLEAN<br>FÁCIL DE LIMPIAR <br>BREATHABLE<br>TRANSPIRABLE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Abrasion Resistance (Martindale)<br>Resistencia a la abrasión (Martindale)               | 25000<br>UNE EN ISO 12497-2:2016                                                                                                                                                                                                                                                                                                                                                                                                      | <br>BLEACH<br>friendly <br>DURABLE<br>is green                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Shrinkage to Washing<br>Encogimiento al lavado                                           | Warp Urdimbre -1,5%<br>Weft Trama 0%<br>UNE EN ISO 5077:2007                                                                                                                                                                                                                                                                                                                                                                          | Optional Finishes<br>Acabados opcionales                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Flammability<br>Inflamabilidad                                                           | UNE 1021 PART 1<br>BS 5852-0 Cigarette Test<br>Cal 117, NFPA 260                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Cleaning Instructions<br>Manutención                                                     |      |  WATERPROOF<br>IMPERMEABLE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

Sensitive values of tolerance +/- 5%. Valores susceptibles de tolerancia de +/- 5%

**5 YEARS WARRANTY**

The Agora warranty covers the fabric becoming unserviceable as a result of loss of colour or strength from normal exposure conditions, including sunlight, mildew, rot and atmospheric chemicals, when properly installed, used and maintained. The warranty does not cover labour and installation costs supplied by the dealer. The warranty neither applies against deterioration of any kind due to abusive use, accidental burns, negligence or perforations. La garantía Agora cubre un anormal deterioro del tejido debido a la pérdida de color o resistencia siempre que existan unas condiciones de exposición normales, incluyendo el sol, moho, putrefacción y químicos de la atmósfera en general, siempre y cuando el tejido haya sido instalado, utilizado y mantenido correctamente. La garantía no cubre los trabajos de instalación del distribuidor. La garantía tampoco cubre, en cualquier caso, el deterioro debido al uso abusivo, quemaduras accidentales, negligencia o perforación.