

|                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Composition</b><br>Composición                                                               | <b>100% Solution Dyed Acrylic</b><br>100% Acrílico Tintado en Masa                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Width</b><br>Ancho                                                                           | <b>153 cm</b><br>60"                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Weight</b><br>Peso                                                                           | <b>310 g/m<sup>2</sup></b><br>9.1 oz/yd <sup>2</sup>                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Length of rolls</b><br>Longitud de las piezas                                                | <b>50 m</b><br>54.7 yd                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Finish</b><br>Acabado                                                                        |  <b>Water Repellent</b><br>Hidrófugo  <b>Anti-Stain</b><br>Antimanchas                                                                                                                                                                                            |
| <b>Colour fastness to light</b><br>Solidez a la luz                                             | <b>7-8/8</b><br>UNE EN ISO 105-B02:2014                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Colour fastness to artificial weathering</b><br>Solidez del color a la intemperie artificial | <b>7-8/8</b><br>UNE-EN ISO 105-B04:1998                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Colour fastness to rubbing</b><br>Solidez de las tinturas al frote                           | <b>4-5/5</b><br>UNE EN ISO 105-X12:2016                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Colour fastness to chlorinated water</b><br>Solidez de las tinturas al agua clorada          | <b>5/5</b><br>UNE EN ISO 105-E03:2010                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Ultraviolet protection factor UPF</b><br>Factor de protección ultravioleta UPF               | <b>50+</b><br>AZ/NZS 4399/1996                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Spray test</b>                                                                               | <b>5/5</b><br>UNE EN ISO 24920                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Water column mm</b><br>Columna de agua mm                                                    | <b>650</b><br>UNE EN ISO 20811                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Tear resistance</b><br>Resistencia al desgarro                                               | <b>Warp Urdimbre 49 N</b><br><b>Weft Trama 32 N</b><br>UNE EN ISO 13937-3:2001                                                                                                                                                                                                                                                                                                                                                      |
| <b>Slippage resistant</b><br>Deslizamiento a la costura                                         | <b>Warp Urdimbre 5,0 mm 0.19"</b><br><b>Weft Trama 3,0 mm 0.12"</b><br>UNE EN ISO 13936-2:2004                                                                                                                                                                                                                                                                                                                                      |
| <b>Tensile strength</b><br>Resistencia a la tracción                                            | <b>Warp Urdimbre 1800 N</b><br><b>Weft Trama 860 N</b><br>UNE EN ISO 13934-1:2013                                                                                                                                                                                                                                                                                                                                                   |
| <b>Shrinkage to washing</b><br>Encogimiento al lavado                                           | <b>Warp Urdimbre -1'5%</b><br><b>Weft Trama 0%</b><br>UNE EN ISO 5077:2007                                                                                                                                                                                                                                                                                                                                                          |
| <b>Cleaning instructions</b><br>Manutención                                                     |      |

## Uses

Usos



## Qualities

Cualidades



Sensitive values of tolerance +/- 5%. Valores susceptibles de tolerancia de +/- 5%.



The Agora warranty covers the fabric becoming unserviceable as a result of loss of colour or strength from normal exposure conditions, including sunlight, mildew, rot and atmospheric chemicals, when properly installed, used and maintained. The warranty does not cover labour and installation costs supplied by the dealer. The warranty neither applies against deterioration of any kind due to abusive use, accidental burns, negligence or perforations.

La garantía Agora cubre un anormal deterioro del tejido debido a la pérdida de color o resistencia siempre que existan unas condiciones de exposición normales, incluyendo el sol, moho, putrefacción y químicos de la atmósfera en general, siempre y cuando el tejido haya sido instalado, utilizado y mantenido correctamente. La garantía no cubre los trabajos de instalación del distribuidor. La garantía tampoco cubre, en cualquier caso, el deterioro debido al uso abusivo, quemaduras accidentales, negligencia o perforación.

