


Composition Composición	92% SDA - 8% Polyester AT 92% SDA - 8% Poliéster AT
Width Ancho	Ext. 17mm - Int. 9mm Ext. 0.7" - Int. 0.4"
Weight Peso	31 g/ml 0.9 oz/yd ²
Finish Acabado	 Water Repellent Hidrófugo  Anti-Stain Antimanchas
Colour fastness to light Solidez a la luz	7/8 UNE EN ISO 105-B02:2014
Colour fastness to artificial weathering Solidez del color a la intemperie artificial	7-8/8 UNE-EN ISO 105-B04:1998
Colour fastness to rubbing Solidez de las tinturas al frote	4-5/5 UNE EN ISO 105-X12:2016
Colour fastness to chlorinated water Solidez de las tinturas al agua clorada	5/5 UNE EN ISO 105-E03:2010
Ultraviolet protection factor UPF Factor de protección ultravioleta UPF	50+ AZ/NZS 4399/1996
Spray test	5/5 UNE EN ISO 24920
Water column mm Columna de agua mm	100 UNE EN ISO 20811
Tear resistance Resistencia al desgarró	Warp Urdimbre 170 N Weft Trama 150 N UNE EN ISO 13937-3:2001
Breaking Strength Resistencia a la rotura	Warp Urdimbre 1900 N Weft Trama 950 N UNE EN ISO 13934-1:2013
Resistance to pilling Resistencia al pilling	4-5/5 UNE EN ISO 12945-2:2001
Abrasion resistance (Martindale) Resistencia a la abrasión (Martindale)	20000 UNE EN ISO 12497-2:2016
Cleaning instructions Manutención	    

Uses

Usos



Qualities

Cualidades



Sensitive values of tolerance +/- 5%. Valores susceptibles de tolerancia de +/- 5%.

5 YEARS WARRANTY

The Agora warranty covers the fabric becoming unserviceable as a result of loss of colour or strength from normal exposure conditions, including sunlight, mildew, rot and atmospheric chemicals, when properly installed, used and maintained. The warranty does not cover labour and installation costs supplied by the dealer. The warranty neither applies against deterioration of any kind due to abusive use, accidental burns, negligence or perforations.

La garantía Agora cubre un anormal deterioro del tejido debido a la pérdida de color o resistencia siempre que existan unas condiciones de exposición normales, incluyendo el sol, moho, putrefacción y químicos de la atmósfera en general, siempre y cuando el tejido haya sido instalado, utilizado y mantenido correctamente. La garantía no cubre los trabajos de instalación del distribuidor. La garantía tampoco cubre, en cualquier caso, el deterioro debido al uso abusivo, quemaduras accidentales, negligencia o perforación.