


Composition Composición	Surface 100% Vinyl Vinilo Backing 100% Polyester Poliéster
Width Ancho	140 cm 54"
Weight Peso	820 g/m ² 17,70 oz/yd ²
Length of rolls Longitud de las piezas	25 m 27,34 yd
Water column Columna de agua	>200 cm UNE EN 20811
Abrasion resistance Resistencia a la abrasión	150.000 Cycles Ciclos
Inflammability Flammabilidad	UNE-EN 1021 Parts 1-2 BS 5852 Cigarette & Match IMO MSC 307 (88)
U.V. Resistance Resistencia U.V.	1.000 Hours Horas
Colour fastness to light Solidez a la luz	6 ISO 105-B02
Breacking Resistance Resistencia a la tracción	N/5 cm ≥ 150 UNE EN ISO 13934-4
Tratamiento antibacteriano Antibacterial Treatment	Si Yes
Cleaning instructions Manutención	    Use neutral soap Utilizar jabón neutro

Uses
Usos



Qualities
Cualidades



Sensitive values of tolerance +/- 7%. Valores susceptibles de tolerancia de +/- 7%



3 YEARS WARRANTY

The Agora warranty covers the fabric becoming unserviceable as a result of loss of colour or strength from normal exposure conditions, including sunlight, mildew, rot and atmospheric chemicals, when properly installed, used and maintained. The warranty does not cover labour and installation costs supplied by the dealer. The warranty neither applies against deterioration of any kind due to abusive use, accidental burns, negligence or perforations. La garantía Agora cubre un anormal deterioro del tejido debido a la pérdida de color o resistencia siempre que existan unas condiciones de exposición normales, incluyendo el sol, moho, putrefacción y químicos de la atmósfera en general, siempre y cuando el tejido haya sido instalado, utilizado y mantenido correctamente. La garantía no cubre los trabajos de instalación del distribuidor. La garantía tampoco cubre, en cualquier caso, el deterioro debido al uso abusivo, quemaduras accidentales, negligencia o perforación.